



Extractors 2009 / 2010

The future moving in.

SIEMENS



Siemens extractors. Fresh air in every kitchen.

Chimney cooker hoods – designed for your kitchen

An absolute "must" in all kitchens, because the cooker hood not only extracts bothersome cooking odours as they occur, but also captures the greasy fumes that would otherwise settle on every surface.

Ducted or recirculated air – whatever is right for your kitchen

With the cooker hoods of the air extraction type, the kitchen air extracted by the fan is ducted to a vent through an outside wall (telescopic wall outlet) or into an air shaft. In contrast to the exhaust-air principle, which exchanges the air in the kitchen, the recirculating system scrubs the cooking fumes by passing them through grease filters and activated charcoal filters. The clean air is then returned to the kitchen.

Flexible design – a wide range for all requirements

Our range of cooker hoods provides the right solution for every kitchen situation. The contemporary styling of our superb line of chimney hoods, for example, adds that professional touch to any kitchen. Island extractors form the centre piece of a kitchen. Situated above independently placed worktops.

Chimney extractors are especially designed to be fitted against walls.

Canopy-style cooker hoods are fitted into specially prepared cupboards.








Extraction power




Maximum extraction is measured with a round pipe 15 Ø cm, 1m high x 3m long pipe at a 90° angle. Recirculation generally reduces extraction by 25% due to the more resistant filter system.




SoftLight

The dimmer function on our SoftLight appliance means that you can regulate the brightness of your work station – soft light to illuminate you kitchen or direct light onto your hob.



	LF359BA80	LF157GA60	LF958TA60
	 ◀ 180 cm ▶	 ◀ 100 cm ▶	 ◀ 90 cm ▶
Product Description	ISLAND EXTRACTOR EXHAUST OR RECIRCULATION OPERATION	ISLAND EXTRACT OR EXHAUST OR RECIRCULATION OPERATION	ISLAND EXTRACTOR EXHAUST OR RECIRCULATION OPERATION
Comfort and Safety	Twin Motors Electronic control via touch controls from both sides 3 Speed settings plus Intensive setting with automatic reset facility Automatic 15 min. run on facility Saturation indicator for metal filter and charcoal filter Metal grease filter, dishwasher safe	Electronic control via touch controls from both sides 3 Speed settings plus Intensive setting with automatic reset facility Automatic 15 min. run on facility Saturation indicator for metal filter and charcoal filter Metal grease filter, dishwasher safe	Electronic control via touch controls from both sides 3 Speed settings plus Intensive setting with automatic reset facility Automatic 10 min. run on facility Saturation indicator for metal filter and charcoal filter Metal grease filter, dishwasher safe
Design	Rimm ventilation Worktop lighting with halogen bulbs (8 x 20 W)	Fourway extraction SoftLight and dimmer function Stainless Steel with Glass Worktop lighting (4 x 20 W)	Rimm Ventilation SoftLight and dimmer function Worktop lighting with halogen bulbs (4 x 20 W)
Minimum Clearance Above Cooking Point	Gas Appliances: 65.0cm Electrical Appliances: 55.0cm	Gas Appliances: 65.0cm Electrical Appliances: 55.0cm	Gas Appliances: 65.0cm Electrical Appliances: 55.0cm
Special Accessories	LZ22120 Wall Duct Box 999120 Flex Hose LZ54250 Recirculation Kit	LZ22120 Wall Duct Box 999120 Flex Hose LZ54050 Recirculation Kit	LZ22120 Wall Duct Box 999120 Flex Hose LZ52850 Recirculation Kit
Product Specs	Height Exhaust (H x W x D): 78.0 –104.0 x 180.0 x 70.0 cm Height Recirc. (H x W x D): 78.0 –104.0 x 180.0 x 70.0 cm Rating: 760W Normal Extraction: 920 m ³ /h Intensive Extraction: 1440 m ³ /h	Height Exhaust (H x W x D): 77.1 –105.1 x 100.0 x 70.0 cm Height Recirc. (H x W x D): 77.1 –109.1 x 100.0 x 70.0 cm Rating: 295W Normal Extraction: 500 m ³ /h Intensive Extraction: 720 m ³ /h Noise Level: 60dB/500 m ³ /h	Height Exhaust (H x W x D): 80.0 –98.0 x 90.0 x 60.0 cm Height Recirc. (H x W x D): 80.0 –110.0 x 90.0 x 60.0 cm Rating: 260W Normal Extraction: 620 m ³ /h Intensive Extraction: 820 m ³ /h Noise Level: 59dB/620 m ³ /h
	LC258TC60	LC957AA70	LC956KA40
	 ◀ 120 cm ▶	 ◀ 90 cm ▶ 	 ◀ 90 cm ▶
Product Description	WALL MOUNTED EXTRACTOR EXHAUST OPERATION ONLY	WALL MOUNTED EXTRACTOR EXHAUST OR RECIRCULATION OPERATION	WALL MOUNTED EXTRACTOR EXHAUST OPERATION ONLY
Comfort and Safety	Electronic control via soft touch push buttons 3 Speed settings plus Intensive setting with automatic reset facility Automatic 10 min. run on facility Saturation indicator for metal filter Metal grease filter, dishwasher safe	Pull-out function 43.0 –65.0cm Electronic control via touch controls 3 Speed settings plus Intensive setting with automatic reset facility Run on facility 10 min Saturation indicator for metal filter and charcoal filter Metal grease filter, dishwasher safe	Electronic control via soft touch push buttons 3 Speed settings plus Intensive setting with automatic reset facility Run on facility 10 min Saturation indicator for metal filter Metal grease filter, dishwasher safe
Design	Worktop lighting with halogen bulbs (4 x 20 W)	SoftLight and dimmer function Worktop lighting with halogen bulbs (4 x 20 W)	SoftLight and dimmer function Worktop lighting with halogen bulbs (3 x 20 W)
Minimum Clearance Above Cooking Point	Gas Appliances: 65.0cm Electrical Appliances: 55.0cm	Gas Appliances: 65.0cm Electrical Appliances: 55.0cm	Gas Appliances: 65.0cm Electrical Appliances: 55.0cm
Special Accessories	LZ22120 Wall Duct Box 999120 Flex Hose	LZ22120 Wall Duct Box 999120 Flex Hose LZ51605 Recirculation Kit	LZ22120 Wall Duct Box 999120 Flex Hose
Product Specs	Height Exhaust (H x W x D): 72.0 –99.0 x 120.0 x 55.0 cm Rating: 300W Normal Extraction: 480 m ³ /h Intensive Extraction: 800 m ³ /h Noise Level: 61dB/480 m ³ /h	Height Exhaust (H x W x D): 67.8 –108.3 x 90.0 x 43.0 –65.0 cm Height Recirc. (H x W x D): 75.3 –116.8 x 90.0 x 43.0 –65.0 cm Rating: 295W Normal Extraction: 500 m ³ /h Intensive Extraction: 700 m ³ /h Noise Level: 63dB/500 m ³ /h	Height Exhaust (H x W x D): 80.0 –108.0 x 90.0 x 48.0 cm Rating: 220W Normal Extraction: 380 m ³ /h Intensive Extraction: 620 m ³ /h Noise Level: 54dB/380 m ³ /h

	LC955GB60	LC957BC40	LC656BB40
	 ◀ 90 cm ▶	 ◀ 90 cm ▶	 ◀ 60 cm ▶
Product Description	WALL MOUNTED EXTRACTOR EXHAUST OR RECIRCULATION OPERATION	WALL MOUNTED EXTRACTOR EXHAUST OR RECIRCULATION OPERATION	WALL MOUNTED EXTRACTOR EXHAUST OR RECIRCULATION OPERATION
Comfort and Safety	Electronic control via touch controls 3 Speed settings plus Intensive setting with automatic reset facility Saturation indicator for metal filter and charcoal filter Metal grease filter, dishwasher safe	Electronic control via soft touch push buttons 3 Speed settings plus Intensive setting with automatic reset facility Metal grease filter, dishwasher safe	Electronic control via soft touch push buttons 3 Speed settings plus Intensive setting with automatic reset facility Metal grease filter, dishwasher safe
Design	Stainless Steel and Glass SoftLight and dimmer function Worktop lighting with halogen bulbs (2 x 20 W)	Worktop lighting with halogen bulbs (3 x 20 W)	Worktop lighting with halogen bulbs (3 x 20 W)
Minimum Clearance Above Cooking Point	Gas Appliances: 65.0cm Electrical Appliances: 55.0cm	Gas Appliances: 65.0cm Electrical Appliances: 55.0cm	Gas Appliances: 65.0cm Electrical Appliances: 55.0cm
Special Accessories	LZ22120 Wall Duct Box 999120 Flex Hose LZ51550 Recirculation Kit	LZ22120 Wall Duct Box 999120 Flex Hose LZ52250 Recirculation Kit	LZ22120 Wall Duct Box 999120 Flex Hose LZ52250 Recirculation Kit
Product Specs	Height Exhaust (H x W x D): 70.0 –108.0 x 90.0 x 52.0 cm Height Recirc. (H x W x D): 78.0 –117.5 x 90.0 x 52.0 cm Rating: 240W Normal Extraction: 470 m ³ /h Intensive Extraction: 590 m ³ /h Noise Level: 62dB/470 m ³ /h	Height Exhaust (H x W x D): 68.4 –108.3 x 90.0 x 50.0 cm Height Recirc. (H x W x D): 65.3 –109.7 x 90.0 x 50.0 cm Rating: 250W Normal Extraction: 650 m ³ /h Intensive Extraction: 770 m ³ /h Noise Level: 65dB/650 m ³ /h	Height Exhaust (H x W x D): 65.3 –98.2 x 60.0 x 50.0 cm Height Recirc. (H x W x D): 65.3 –109.7 x 60.0 x 50.0 cm Rating: 240W Normal Extraction: 500 m ³ /h Intensive Extraction: 640 m ³ /h Noise Level: 65dB/500 m ³ /h

	LC654BB20	LB75564	LB54564
	 ◀ 60 cm ▶	 ◀ 70 cm ▶	 ◀ 60 cm ▶
Product Description	WALL MOUNTED EXTRACTOR EXHAUST OR RECIRCULATION OPERATION	CANOPY EXTRACTOR EXHAUST OR RECIRCULATION OPERATION	CANOPY EXTRACTOR EXHAUST OR RECIRCULATION OPERATION
Comfort and Safety	Control via Push Buttons 3 Speed settings Metal grease filter, dishwasher safe	Metal filter with aluminium frame 2 powerful motors 3 settings plus 1 intensive setting	Metal filter with aluminium frame 2 powerful motors 3 settings plus 1 intensive setting
Design	Worktop lighting with halogen bulbs (2 x 20 W)	Fully integrated Worktop lighting with halogen bulbs (2 x 20 W)	Fully integrated Worktop lighting with halogen bulbs (2 x 20 W)
Minimum Clearance Above Cooking Point	Gas Appliances: 65.0cm Electrical Appliances: 55.0cm	Gas Appliances: 65.0cm Electrical Appliances: 55.0cm	Gas Appliances: 65.0cm Electrical Appliances: 55.0cm
Special Accessories	LZ22120 Wall Duct Box 999120 Flex Hose LZ52250 Recirculation Kit	LZ22120 Wall Duct Box 999120 Flex Hose LZ73050 Recirculation Kit	LZ22120 Wall Duct Box 999120 Flex Hose LZ73050 Recirculation Kit
Product Specs	Height Exhaust (H x W x D): 65.3 –98.2 x 60.0 x 50.0 cm Height Recirc. (H x W x D): 65.3 –109.7 x 60.0 x 50.0 cm Rating: 240W Normal Extraction: 460 m ³ /h Noise Level: 65dB/460 m ³ /h	Height Exhaust (H x W x D): 25.5 x 73.0 x 38.0 cm Height Recirc. (H x W x D): 25.5 x 73.0 x 38.0 cm Rating: 240W Normal Extraction: 400 m ³ /h Intensive Extraction: 650 m ³ /h Noise level: 59 dB/400 m ³ /h	Overall (H x W x D): 30.0 x 53.0 x 37.0 cm Rating: 380 W Normal Extraction: 400 m ³ /h Intensive Extraction: 500 m ³ /h Noise level: 62 dB/400 m ³ /h



3 YEAR
GUARANTEE
FREESTANDING APPLIANCES
SIEMENS



5 YEAR
GUARANTEE
BUILT-IN APPLIANCES
SIEMENS

The world around us has become a myriad of change and confusion. We are constantly being cluttered with contradictions and complications that we somehow have to sort through on a daily basis, certain traits have however managed to stand out above the rest and rise out from the clutter.

Quality and style happen to be two of these most sought after traits in today's society. Traits that are truly worth searching for, worth waiting for, and unfortunately far too rare in a world that all too often manages to confuse what is really important to us in our daily lives.

It is this often-illusory search for true quality and style that leads us to something special. The Siemens 3 and 5 Year Guarantee is truly something special. The name Siemens epitomizes true quality and guarantees that you can move into the future with style and confidence.

Midrand

Siemens Domestic Appliances
Private Bag X36
Randjespark
Halfway House 1685
Rep. of South Africa

Visitors:

Fifteenth Road
Randjespark
Midrand

Tel: (011) 265-7800
Fax: (011) 265-7817

Cape Town

Siemens Domestic Appliances
Post Net Suite #248
Private Bag X19,
Milnerton 7435
Rep. of South Africa

Visitors:

Shop No. 1, Marconi Centre
460 Koeberg Road,
Milnerton 7441

Tel: (021) 550-9900
Fax: (021) 552-9205/6

BSH Service Centre

Tel: 0860 026 724
Fax: 0861 171 780
E-mail: applianceserviceza@bshg.com
E-mail: callcentre@anvilconstult.co.za

Spare Parts

Tel: (011) 265-7853
Fax: (011) 265-7850

www.siemensappliances.co.za

Please note that certain features apply to particular products.
No responsibility can be accepted for printing errors.